



Ford Fuel Injector Calibration Summary

PN: 16mx-20-1200-8, 16mx-21-1200-8, 16mx-23-1200-8, 16mx-20-1200-6

Scalars		
	40 psi	55 psi
Fuel Injector Breakpoint	0.0000127	0.0000223
Fuel Injector High Slope	0.0283347	0.0334941
Fuel Injector Low Slope	0.0624636	0.0406760
Fuel Injector Minimum Pulsewidth	0.0000725	0.0002500
Max Allowed Inj Duty Cycle	1.999	1.999
Max Allowed Inj Duty Cycle on Alcohol	2.000	2.000

Low Slope Multiplier	
DeltaP	Multiplier
60.03	1.0000
54.96	1.0000
50.03	1.0000
39.15	1.0000
30.02	1.0000
20.01	1.0000

Breakpoint Multiplier	
DeltaP	Multiplier
60.03	1.0000
54.96	1.0000
50.03	1.0000
39.15	1.0000
30.02	1.0000
20.01	1.0000

Injector Comp Batt Volt Offset		
Battery_Voltage	40 psi	55 psi
15	0.000924	0.001040
14	0.001000	0.001190
13	0.001117	0.001370
12	0.001275	0.001580
11	0.001474	0.001820
10	0.001714	0.002090
8	0.002317	0.002730
6	0.002417	0.003500

High Slope Multiplier	
DeltaP	Multiplier
60.03	1.0000
54.96	1.0000
50.03	1.0000
39.15	1.0000
30.02	1.0000
20.01	1.0000

Batt Comp Multiplier	
Pressure	Multiplier
60.03	1.0000
54.96	1.0000
50.03	1.0000
44.95	1.0000
39.15	1.0000
30.02	1.0000
20.01	1.0000

Note: If SCT programmer will not allow input of certain values above, you may need to disable "Check MIN/MAX value limits" located in "Options Dialog"
 REV: 1-30-19