



Holley EFI Injector Data

DW PN: 16M-XX-1500-X

| 29.0 PSI (2 BAR) | | | | | | | | | | | | | | | | |
|----------------------|----------------|------|--------------------------------|------|------|-------------|------|------|--------------------------------|------|--------|------|------|------|------|------|
| Voltage | 8.0 | 8.5 | 9.6 | 10.4 | 11.2 | 12.0 | 12.8 | 13.6 | 14.4 | 15.2 | 16.0 | 16.8 | 17.6 | 18.4 | 19.2 | 20.0 |
| Off Time | 1.83 | 1.71 | 1.48 | 1.32 | 1.18 | 1.04 | 0.91 | 0.79 | 0.68 | 0.58 | 0.49 | 0.41 | 0.45 | 0.39 | 0.39 | 0.38 |
| Injector Type | High Impedance | | Rated Flow Per Injector | | | 118.6 LB/HR | | | Rated Injector Pressure | | 29 PSI | | | | | |

| 43.5 PSI (3 BAR) | | | | | | | | | | | | | | | | |
|----------------------|----------------|------|--------------------------------|------|------|-------------|------|------|--------------------------------|------|----------|------|------|------|------|------|
| Voltage | 8.0 | 8.5 | 9.6 | 10.4 | 11.2 | 12.0 | 12.8 | 13.6 | 14.4 | 15.2 | 16.0 | 16.8 | 17.6 | 18.4 | 19.2 | 20.0 |
| Off Time | 2.19 | 2.03 | 1.71 | 1.50 | 1.31 | 1.14 | 0.99 | 0.86 | 0.75 | 0.66 | 0.59 | 0.54 | 0.52 | 0.50 | 0.49 | 0.49 |
| Injector Type | High Impedance | | Rated Flow Per Injector | | | 145.7 LB/HR | | | Rated Injector Pressure | | 43.5 PSI | | | | | |

| 58 PSI (4 BAR) | | | | | | | | | | | | | | | | |
|----------------------|----------------|------|--------------------------------|------|------|-------------|------|------|--------------------------------|------|--------|------|------|------|------|------|
| Voltage | 8.0 | 8.5 | 9.6 | 10.4 | 11.2 | 12.0 | 12.8 | 13.6 | 14.4 | 15.2 | 16.0 | 16.8 | 17.6 | 18.4 | 19.2 | 20.0 |
| Off Time | 2.65 | 2.46 | 2.05 | 1.79 | 1.56 | 1.34 | 1.16 | 1.00 | 0.86 | 0.76 | 0.67 | 0.61 | 0.59 | 0.57 | 0.56 | 0.55 |
| Injector Type | High Impedance | | Rated Flow Per Injector | | | 170.4 LB/HR | | | Rated Injector Pressure | | 58 PSI | | | | | |

| 72.5 PSI (5 BAR) | | | | | | | | | | | | | | | | |
|----------------------|----------------|------|--------------------------------|------|------|-------------|------|------|--------------------------------|------|----------|------|------|------|------|------|
| Voltage | 8.0 | 8.5 | 9.6 | 10.4 | 11.2 | 12.0 | 12.8 | 13.6 | 14.4 | 15.2 | 16.0 | 16.8 | 17.6 | 18.4 | 19.2 | 20.0 |
| Off Time | 3.34 | 3.07 | 2.54 | 2.20 | 1.89 | 1.62 | 1.39 | 1.20 | 1.05 | 0.93 | 0.86 | 0.81 | 0.78 | 0.76 | 0.74 | 0.74 |
| Injector Type | High Impedance | | Rated Flow Per Injector | | | 196.4 LB/HR | | | Rated Injector Pressure | | 72.5 PSI | | | | | |