



Ford Fuel Injector Calibration Summary

PN: 16m-20-1500-8, 16m-21-1500-8 16m-23-1500-8

Scalars		
	40 psi	55 psi
Fuel Injector Breakpoint	0.0000216	0.0000263
Fuel Injector High Slope	0.0384943	0.0434301
Fuel Injector Low Slope	0.0897762	0.0659917
Fuel Injector Minimum Pulsewidth	0.0002500	0.0003878
Max Allowed Inj Duty Cycle	1.999	1.999
Max Allowed Inj Duty Cycle on Alcohol	2.000	2.000

Low Slope Multiplier	
DeltaP	Multiplier
60.03	1.0000
54.96	1.0000
50.03	1.0000
39.15	1.0000
30.02	1.0000
20.01	1.0000

Breakpoint Multiplier	
DeltaP	Multiplier
60.03	1.0000
54.96	1.0000
50.03	1.0000
39.15	1.0000
30.02	1.0000
20.01	1.0000

Injector Comp Batt Volt Offset		
Battery_Voltage	40 psi	55 psi
15	0.000901	0.000959
14	0.000970	0.001038
13	0.001073	0.001162
12	0.001210	0.001326
11	0.001381	0.001536
10	0.001586	0.001786
8	0.002098	0.002417
6	0.002198	0.002517

High Slope Multiplier	
DeltaP	Multiplier
60.03	1.0000
54.96	1.0000
50.03	1.0000
39.15	1.0000
30.02	1.0000
20.01	1.0000

Batt Comp Multiplier	
Pressure	Multiplier
60.03	1.0000
54.96	1.0000
50.03	1.0000
44.95	1.0000
39.15	1.0000
30.02	1.0000
20.01	0.9310

Note: If SCT programmer will not allow input of certain values above, you may need to disable "Check MIN/MAX value limits" located in "Options Dialog"

REV: 1-30-19