



Ford Fuel Injector Calibration Summary

PN: 17u-00-0095-8, 17u-04-0095-8, 17u-05-0095-8

Scalars		
	40 psi	55 psi
Fuel Injector Breakpoint	0.0000125	0.0000246
Fuel Injector High Slope	0.0232300	0.0283224
Fuel Injector Low Slope	0.0309500	0.0378552
Fuel Injector Minimum Pulsewidth	0.0002500	0.0002720
Max Allowed Inj Duty Cycle	1.999	1.999
Max Allowed Inj Duty Cycle on Alcohol	2.000	2.000

Low Slope Multiplier	
DeltaP	Multiplier
60.03	1.0000
54.96	1.0000
50.03	1.0000
39.15	1.0000
30.02	1.0000
20.01	1.0000

Breakpoint Multiplier	
DeltaP	Multiplier
60.03	1.0000
54.96	1.0000
50.03	1.0000
39.15	1.0000
30.02	1.0000
20.01	1.0000

Injector Comp Batt Volt Offset		
Battery_Voltage	40 psi	55 psi
15	0.000943	0.000992
14	0.001009	0.001066
13	0.001112	0.001185
12	0.001252	0.001348
11	0.001429	0.001555
10	0.001642	0.001806
8	0.002180	0.002442
6	0.002280	0.002542

High Slope Multiplier	
DeltaP	Multiplier
60.03	1.0000
54.96	1.0000
50.03	1.0000
39.15	1.0000
30.02	1.0000
20.01	1.0000

Batt Comp Multiplier	
Pressure	Multiplier
60.03	1.0000
54.96	1.0000
50.03	1.0000
44.95	1.0000
39.15	1.0000
30.02	1.0000
20.01	1.0000

Note: If SCT programmer will not allow input of certain values above, you may need to disable "Check MIN/MAX value limits" located in "Options Dialog"

REV: 1-30-19