



Ford Fuel Injector Calibration Summary

PN: 18u-00-0060-8, 18u-01-0060-8, 18u-00-0060-6

| Scalars | |
|---------------------------------------|-----------|
| Fuel Injector Breakpoint | 0.0000111 |
| Fuel Injector High Slope | 0.0179608 |
| Fuel Injector Low Slope | 0.0229263 |
| Fuel Injector Minimum Pulsewidth | 0.0002500 |
| Max Allowed Inj Duty Cycle | 1.999 |
| Max Allowed Inj Duty Cycle on Alcohol | 2.000 |

| Injector Comp Batt Volt Offset | |
|--------------------------------|----------|
| Battery_Voltage | PW_sec |
| 15 | 0.000985 |
| 14 | 0.001048 |
| 13 | 0.001151 |
| 12 | 0.001292 |
| 11 | 0.001473 |
| 10 | 0.001692 |
| 8 | 0.002259 |
| 6 | 0.002350 |

| Low Slope Multiplier | |
|----------------------|------------|
| DeltaP | Multiplier |
| 60.03 | 1.4006 |
| 54.96 | 1.3033 |
| 50.03 | 1.2087 |
| 39.15 | 1.0000 |
| 30.02 | 0.8248 |
| 20.01 | 0.6328 |

| High Slope Multiplier | |
|-----------------------|------------|
| DeltaP | Multiplier |
| 60.03 | 1.3094 |
| 54.96 | 1.2343 |
| 50.03 | 1.1612 |
| 39.15 | 1.0000 |
| 30.02 | 0.8647 |
| 20.01 | 0.7164 |

| Breakpoint Multiplier | |
|-----------------------|------------|
| DeltaP | Multiplier |
| 60.03 | 1.3711 |
| 54.96 | 1.2810 |
| 50.03 | 1.1933 |
| 39.15 | 1.0000 |
| 30.02 | 0.8378 |
| 20.01 | 0.6599 |

| Batt Comp Multiplier | |
|----------------------|------------|
| Pressure | Multiplier |
| 60.03 | 1.1076 |
| 54.96 | 1.0815 |
| 50.03 | 1.0561 |
| 44.95 | 1.0280 |
| 39.15 | 1.0000 |
| 30.02 | 0.9530 |
| 20.01 | 0.9014 |

Note: If SCT programmer will not allow input of certain values above, you may need to disable "Check MIN/MAX value limits" located in "Options Dialog
REV: 1-30-19