



Ford Fuel Injector Calibration Summary

PN: 18u-00-0060-8, 18u-01-0060-8, 18u-00-0060-6

Scalars	
Fuel Injector Breakpoint	0.0000111
Fuel Injector High Slope	0.0179608
Fuel Injector Low Slope	0.0229263
Fuel Injector Minimum Pulsewidth	0.0002500
Max Allowed Inj Duty Cycle	1.999
Max Allowed Inj Duty Cycle on Alcohol	2.000

Injector Comp Batt Volt Offset	
Battery_Voltage	PW_sec
15	0.000985
14	0.001048
13	0.001151
12	0.001292
11	0.001473
10	0.001692
8	0.002259
6	0.002350

Low Slope Multiplier	
DeltaP	Multiplier
60.03	1.4006
54.96	1.3033
50.03	1.2087
39.15	1.0000
30.02	0.8248
20.01	0.6328

High Slope Multiplier	
DeltaP	Multiplier
60.03	1.3094
54.96	1.2343
50.03	1.1612
39.15	1.0000
30.02	0.8647
20.01	0.7164

Breakpoint Multiplier	
DeltaP	Multiplier
60.03	1.3711
54.96	1.2810
50.03	1.1933
39.15	1.0000
30.02	0.8378
20.01	0.6599

Batt Comp Multiplier	
Pressure	Multiplier
60.03	1.1076
54.96	1.0815
50.03	1.0561
44.95	1.0280
39.15	1.0000
30.02	0.9530
20.01	0.9014

Note: If SCT programmer will not allow input of certain values above, you may need to disable "Check MIN/MAX value limits" located in "Options Dialog
 REV: 1-30-19