



Holley HP and Dominator EFI Injector Data

DW PN: 16U-XX-0050-X

Minimum Injector Opening Time	0.725 msec
--------------------------------------	------------

29.0 PSI (2 BAR)																
Injector Type		High Impedance				Rated Flow Per Injector			40.1 LB/HR			Rated Injector Pressure		29 PSI		
Off Time	1.96	1.81	1.49	1.29	1.10	0.93	0.78	0.65	0.54	0.44	0.37	0.31	0.27	0.25	0.25	0.25
Voltage	8.0	8.5	9.6	10.4	11.2	12.0	12.8	13.6	14.4	15.2	16.0	16.8	17.6	18.4	19.2	20.0

43.5 PSI (3 BAR)																
Injector Type		High Impedance				Rated Flow Per Injector			54.4 LB/HR			Rated Injector Pressure		43.5 PSI		
Off Time	1.88	1.75	1.49	1.32	1.15	1.00	0.86	0.73	0.62	0.51	0.42	0.33	0.26	0.20	0.16	0.12
Voltage	8.0	8.5	9.6	10.4	11.2	12.0	12.8	13.6	14.4	15.2	16.0	16.8	17.6	18.4	19.2	20.0

58 PSI (4 BAR)																
Injector Type		High Impedance				Rated Flow Per Injector			63.5 LB/HR			Rated Injector Pressure		58 PSI		
Off Time	2.31	2.14	1.79	1.56	1.35	1.16	0.99	0.85	0.72	0.61	0.52	0.46	0.41	0.39	0.38	0.38
Voltage	8.0	8.5	9.6	10.4	11.2	12.0	12.8	13.6	14.4	15.2	16.0	16.8	17.6	18.4	19.2	20.0

72.5 PSI (5 BAR)																
Injector Type		High Impedance				Rated Flow Per Injector			71.8 LB/HR			Rated Injector Pressure		72.5 PSI		
Off Time	2.58	2.37	1.96	1.69	1.46	1.26	1.09	0.95	0.84	0.76	0.72	0.71	0.70	0.69	0.68	0.68
Voltage	8.0	8.5	9.6	10.4	11.2	12.0	12.8	13.6	14.4	15.2	16.0	16.8	17.6	18.4	19.2	20.0