



Ford Fuel Injector Calibration Summary

PN: 18u-00-0088-8, 18u-01-0088-8, 18u-00-0088-6

Scalars	
Fuel Injector Breakpoint	0.0000100
Fuel Injector High Slope	0.0247500
Fuel Injector Low Slope	0.0596350
Fuel Injector Minimum Pulsewidth	0.0002500
Max Allowed Inj Duty Cycle	1.999
Max Allowed Inj Duty Cycle on Alcohol	2.000

Injector Comp Batt Volt Offset	
Battery_Voltage	PW_sec
15	0.001000
14	0.001069
13	0.001187
12	0.001353
11	0.001568
10	0.001830
8	0.002512
6	0.002612

Low Slope Multiplier	
DeltaP	Multiplier
60.03	1.1797
54.96	1.1361
50.03	1.0936
39.15	1.0000
30.02	0.9214
20.01	0.8353

High Slope Multiplier	
DeltaP	Multiplier
60.03	1.3150
54.96	1.2385
50.03	1.1641
39.15	1.0000
30.02	0.8623
20.01	0.7113

Breakpoint Multiplier	
DeltaP	Multiplier
60.03	1.3499
54.96	1.2650
50.03	1.1823
39.15	1.0000
30.02	0.8470
20.01	0.6792

Batt Comp Multiplier	
Pressure	Multiplier
60.03	1.0787
54.96	1.0596
50.03	1.0410
44.95	1.0205
39.15	1.0000
30.02	0.9656
20.01	0.9279

Note: If SCT programmer will not allow input of certain values above, you may need to disable "Check MIN/MAX value limits" located in "Options Dialog"
 REV: 1-30-19

