



## Ford Fuel Injector Calibration Summary

**PN: 18u-00-0078-8, 18u-01-0078-8, 18u-00-0078-6**

Scalars	
Fuel Injector Breakpoint	0.0000072
Fuel Injector High Slope	0.0220000
Fuel Injector Low Slope	0.0350000
Fuel Injector Minimum Pulsewidth	0.0002500
Max Allowed Inj Duty Cycle	1.999
Max Allowed Inj Duty Cycle on Alcohol	2.000

Injector Comp Batt Volt Offset	
Battery_Voltage	PW_sec
15	0.000932
14	0.000994
13	0.001099
12	0.001248
11	0.001439
10	0.001675
8	0.002276
6	0.002376

Low Slope Multiplier	
DeltaP	Multiplier
60.03	1.5661
54.96	1.4657
50.03	1.3453
39.15	1.0000
30.02	0.6257
20.01	0.1268

High Slope Multiplier	
DeltaP	Multiplier
60.03	1.3237
54.96	1.2476
50.03	1.1721
39.15	1.0000
30.02	0.8499
20.01	0.6795

Breakpoint Multiplier	
DeltaP	Multiplier
60.03	1.1907
54.96	1.1333
50.03	1.0843
39.15	1.0000
30.02	0.9544
20.01	0.9309

Batt Comp Multiplier	
Pressure	Multiplier
60.03	1.0943
54.96	1.0771
50.03	1.0569
44.95	1.0284
39.15	1.0000
30.02	0.9393
20.01	0.8592

Note: If SCT programmer will not allow input of certain values above, you may need to disable "Check MIN/MAX value limits" located in "Options Dialog"  
 REV: 1-30-19

