



Holley EFI Injector Data

DW PN: 16S-XX-2200-X

29.0 PSI (2 BAR)																
Voltage	8.0	8.5	9.6	10.4	11.2	12.0	12.8	13.6	14.4	15.2	16.0	16.8	17.6	18.4	19.2	20.0
Off Time	1.39	1.28	1.05	0.90	0.76	0.64	0.52	0.42	0.33	0.25	0.18	0.13	0.08	0.05	0.04	0.03
Injector Type	High Impedance		Rated Flow Per Injector			173 LB/HR			Rated Injector Pressure		29 PSI					

43.5 PSI (3 BAR)																
Voltage	8.0	8.5	9.6	10.4	11.2	12.0	12.8	13.6	14.4	15.2	16.0	16.8	17.6	18.4	19.2	20.0
Off Time	1.62	1.49	1.22	1.04	0.88	0.74	0.61	0.50	0.41	0.33	0.27	0.23	0.20	0.19	0.20	0.22
Injector Type	High Impedance		Rated Flow Per Injector			213.9 LB/HR			Rated Injector Pressure		43.5 PSI					

58 PSI (4 BAR)																
Voltage	8.0	8.5	9.6	10.4	11.2	12.0	12.8	13.6	14.4	15.2	16.0	16.8	17.6	18.4	19.2	20.0
Off Time	1.81	1.70	1.38	1.18	1.00	0.85	0.72	0.62	0.54	0.49	0.45	0.42	0.40	0.40	0.42	0.46
Injector Type	High Impedance		Rated Flow Per Injector			261 LB/HR			Rated Injector Pressure		58 PSI					

72.5 PSI (5 BAR)																
Voltage	8.0	8.5	9.6	10.4	11.2	12.0	12.8	13.6	14.4	15.2	16.0	16.8	17.6	18.4	19.2	20.0
Off Time	2.00	1.86	1.57	1.38	1.22	1.07	0.94	0.84	0.75	0.68	0.63	0.61	0.60	0.61	0.64	0.69
Injector Type	High Impedance		Rated Flow Per Injector			276 LB/HR			Rated Injector Pressure		72.5 PSI					