



4G63 EcuFlash Injector Settings

42m-02-800-4									
Gas Scaling Value (cc/min)	622								
Battery Voltage Latency	Battery Voltage (v)	4.69	7.03	9.38	11.72	14.06	16.41	18.68	
Compensation	Latency (ms)	3.504	1.872	1.224	0.864	0.624	0.456	0.336	

42m-02-1000-4									
Gas Scaling Value (cc/min)	731								
E85 Scaling Value (cc/min)	542								
Battery Voltage Latency	Battery Voltage (v)	4.69	7.03	9.38	11.72	14.06	16.41	18.68	
Compensation	Latency (ms)	2.640	1.848	1.296	0.888	0.576	0.360	0.168	

42m-02-1200-4										
Gas Scaling Value (cc/min)	886									
E85 Scaling Value (cc/min)	696									
Battery Voltage Latency	Battery Voltage (v)	4.69	7.03	9.38	11.72	14.06	16.41	18.68		
Compensation	Latency (ms)	3.384	1.584	1.272	1.032	0.864	0.696	0.672		
Cranking Enrichment IPW Adder (main)	Coolant Temp (c)	-32	-18	-8	7	20	34	50	72	82
	Gas (ms)	224.3	106.1	44.1	15.3	13.4	10.4	4.7	1.0	1.0
	e85 (ms)	236.3	118.1	56.1	29.3	27.4	24.4	11.7	1.0	1.0

42m-02-1800-4										
Gas Scaling Value (cc/min)										
E85 Scaling Value (cc/min)										
Battery Voltage Latency	Battery Voltage (v)	4.69	7.03	9.38	11.72	14.06	16.41	18.68		
Compensation	Latency (ms)									
Cranking Enrichment IPW Adder (main)	Coolant Temp (c)	-32	-18	-8	7	20	34	50	72	82
	Gas (ms)									
	e85 (ms)									

NOTES:

All other fuel injector related values should be left at their OE values

rev 3-6-17

© DeatschWerks, LLC - 2015 - all rights reserved