



Ford Fuel Injector Calibration Summary

PN: 17u-00-0072-8, 17u-04-0072-8, 17u-05-0072-8

Applications: 2011-Current Mustang GT and V6, 2011-Current F150 2011-Current SVT Raptor

Scalars	
Fuel Injector Breakpoint	0.0000158
Fuel Injector High Slope	0.0218000
Fuel Injector Low Slope	0.0284000
Fuel Injector Minimum Pulsewidth	0.0005230
Max Allowed Inj Duty Cycle	1.999
Max Allowed Inj Duty Cycle on Alcohol	2.000

Injector Comp Batt Volt Offset	
Battery_Voltage	PW_sec
15.0	0.000930
14.5	0.000986
14.0	0.001044
13.5	0.001107
13.0	0.001170
12.0	0.001335
11.0	0.001549
10.0	0.001828
9.0	0.002379
8.0	0.002930
7.0	0.005322
6.0	0.007714

Low Slope Multiplier	
DeltaP	Multiplier
67.010	1.0435
63.958	1.0196
58.020	0.9710
54.970	0.9452
50.040	0.9017
45.000	0.8551

High Slope Multiplier	
DeltaP	Multiplier
67.010	1.0435
63.958	1.0196
58.020	0.9710
54.970	0.9452
50.040	0.9017
45.000	0.8551

Breakpoint Multiplier	
DeltaP	Multiplier
67.010	1.0436
63.958	1.0196
58.020	0.9711
54.970	0.9453
50.040	0.9018
45.000	0.8552

Batt Comp Multiplier	
Pressure	Multiplier
67.010	1.0435
63.958	1.0196
58.020	0.9710
54.970	0.9452
50.040	0.9017
45.000	0.8510
41.000	0.8123

Note: If SCT programmer will not allow input of certain values above, you may need to disable "Check MIN/MAX value limits" located in "Options Di:
REV: 1-30-19