



PART NUMBER: TFS-32603001 ENGINE: General Motors Gen IV 6.2L

GRIND: 199995-TFS

VALVE SETTING:		INTAKE:	EXHAUST:		
<b>LIFT:</b>	INTAKE @ CAM	0.368	@ VALVE	0.625	<b>ROCKER ARM RATIO</b>
	EXHAUST @ CAM	0.368	@ VALVE	0.625	1.70
<small>ALL LIFTS ARE BASED ON ZERO LASH AND THEORETICAL ROCKER ARM RATIOS</small>					
<b>CAM TIMING</b>		<b>OPENS</b>		<b>CLOSES</b>	<b>ADV. DURATION</b>
@ .006	INTAKE	29° BTDC		69° ABDC	278°
LIFT	EXHAUST	79° BBDC		27° ATDC	286°
<b>CAM TIMING</b>		<b>OPENS</b>		<b>CLOSES</b>	<b>CENTERLINE</b>
@ .050	INTAKE	5° BTDC		45° ABDC	110°
LIFT	EXHAUST	55° BBDC		3° ATDC	116°
<b>BASIC OPERATING RPM RANGE:</b>		<b>MIN</b>	3000	<b>MAX</b>	7000
<b>LOBE SEPARATION:</b>		113°			
<p><b>This camshaft is not compatible with the Active Fuel Management™ (Displacement on Demand) technology. A delete kit and disabling the system in the ECM is required.</b></p>					

TFS-INS-32603001 Rev.0